



PHABRIX[®]
broadcast excellence

**AVAILABLE
NOW**

OPTION

SDI ANALYSIS

The SDI analysis option provides the engineer with a detailed view of the data words contained within the SDI stream. This allows the analysis of complex faults and is particularly useful when determining compatibility issues between equipment and when debugging new product developments within an R&D environment. Detail within the active SDI stream can be viewed with continuous update. Analysis can be obtained from the generated or received SDI stream allowing quick comparison checks.

A number of screen displays are provided for analysis.

GRID

With reference to pixels at the top of the screen and lines along the left side of the screen, users can look within an x, y grid of pixel and ancillary data. Samples can be viewed as 8 or 10 bit, hex or decimal. Navigation is simple and fast using the thumb pad with the selected value highlighted in white. A separate entry box allows a specific line and sample to be selected. Both the background and foreground text colours are coded for ease of identification. The background colour at any time represents the FVH bits within the TRS words. In this way the operator can determine if a data element is active picture, vertical blanking, horizontal blanking, field 1, field 2 or TRS. The foreground colour gives an indication of the type of pixel data being viewed – Y, Cb, Cr, R, G or B.

STREAM

This allows the SDI continuous stream to be viewed. SD-SDI signals are represented by a 10 bit stream and HD/3G-SDI by a 20 bit stream. A further column provides information to aid the user in identifying data types.

COMPONENT

The component view splits the display into 3 columns displaying Y, Cb and Cr data as 10/8 bit, hex or decimal.

SPLIT


This mode splits the SDI stream further into the components 'Cb Y Cr Y' as 10/8 bit, binary, hex or decimal.

ANCILLARY DATA

This separate window allows the user to capture whole Ancillary data packets identified by their data id (DID). Entering a known DID value or by selecting its descriptive text, the Ancillary packet will be continuously displayed if present within the SDI signal. Data values containing errors found will be displayed in red text. The data may be frozen on screen once captured. There is also a freeze on error check box.

Option code

PHSXOSD



Grid view of the SDI stream showing coloured window sections and highlighted value selected

FEATURE HIGHLIGHTS

- DETAILED DATA WORDS IN SDI STREAM
- CONTINUOUS UPDATE
- SELECTABLE VIEWS, GRID, STREAM COMPONENT, SPLIT
- DATA ID (DID) ANCIALLY PACKET VIEW
- SUPERIOR EASE OF USE

APPLICATIONS

- R&D/TEST DEPARTMENTS
- SYSTEM INTEGRATORS
- SUPPORT ENGINEERS

AVAILABLE FOR

- PHABRIX[®] SxA
- PHABRIX[®] SxD
- PHABRIX[®] SxE
- PHABRIX[®] Rx



PHABRIX[®] Limited
Blindmans Gate Cottage Woolton Hill Newbury
Hampshire RG20 9XB UK
tel/fax + 44 (0)1635 255 494
email: info@phabrix.com www.phabrix.com

